

# **Technical** Data Sheet



## **Typical Inspection Data:**

Density @ 20°C	0.880 g/cm3
Viscosity @ 100°C	14.0 cSt
Viscosity @ 40°C	129 cSt
Phosphorus	0.03%
Colour	Brown
Pour Point	-30°C

## **Performance Profile:**

Recommended by Comma for certain applications where an 80W-90 or 85W-90 API GL-5 oil is specified. Suitable for use where the following specifications are called for:

API GL-5	Ford M2C197-A
MB 235.0	

# EP80W-90 GL-5

# **Mineral**

### **Product Features:**

- Extreme pressure gear oil for manual gearboxes and differentials.
- Recommended by Comma for applications requiring an 80W-90 or 85W-90 API GL-5 oil.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

## Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

#### Pack Size Availability:



15-06-2016

Email: sales@commaoil.com www.CommaOil.com