



Typical Inspection Data:

Density @ 20°C	1.122 g/cm3
Appearance	Clear bright red liquid
Boiling Point	170°C

Protection Levels:

Super Longlife Red (%)	Approx. Protection (°C)
33	-18
50	-36
60	-52

Super Longlife Red Concentrate

Recommended by Comma for applications requiring:

Audi/Seat/Skoda/VW (TL774D); Ford WSS-M97B44-D; MB 325.3; Renault 41-01001

Product Features:

- A Mono Ethylene Glycol (MEG) based engine coolant / anti-freeze concentrate.
- Suitable for petrol and diesel engines.
- 5 Year Longlife Protection.
- Protects against freezing and overheating.
- NAP (Nitrite, Phosphate and Amine), Silicate and Borax free.
- Organic Acid (OAT) Technology.
- Conforms to: BS6580:2010

Directions for use:

- Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
- Pour into vehicle cooling system.
- Miscible with other fluids but for maximum protection systems should be drained, flushed and refilled.
- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Remove spills from paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

20-11-2014